

JUL 31 2007

N

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 56-132828

(43)Date of publication of application : 17.10.1981

(51)Int.Cl.

H04B 7/08

(21)Application number : 55-036299

(71)Applicant : NIPPON TELEGR & TELEPH
CORP <NTT>

(22)Date of filing : 24.03.1980


(72)Inventor : TAJIMA KOJIRO
KOMAKI SHOZO
OKAMOTO SHIGEHARU

(54) SPACE DIVERSITY RECEIVING DEVICE

(57)Abstract:

PURPOSE: To prevent an omission of a picture frame synchronizing signal, by detecting a resultant power level of the space diversity receiving device through the narrow band filter of specific frequency.

CONSTITUTION: Signals which have been received by the main and subsidiary antennas of 1 and 2 are synthesized by the power compounding device 5 through the phase shifter 3 and the phase modulator 4, respectively, also the composite signal is converted to an intermediate frequency signal by the receiving local oscillator 7 and the frequency mixer 6, is amplified by the preamplifier 8, and is provided to the main intermediate amplifier 9 having an AGC function. After that, the output of the preamplifier 8 is partially provided to the level detector 15 through the narrow band filter 14, and its output is inputted to the phase detector 12. The level of said level detector 15 is a level of passing frequency of the filter 14, and by handling this detector output in the same way as regular AGC voltage, in-phase synthesis is executed by said frequency.



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]